



GRESHAM



# DOC TABLES

PRODUCT DATA SPECIFICATION



GRESHAM

# DOC TABLES

## PRODUCT DATA SPECIFICATION

Doc table interlock and are designed to facilitate small group and collaborative work.

### Material

Top panel 25mm Thick Melamine faced chipboard. Tops are edged all around with 2mm thick impact resistant ABS.

Metal continuous welded frame manufactured from 50mm diameter mild steel tube with a 40mm x 25mm under frame. All steel profiles have a minimum wall thickness of 1.5mm.

Metalwork is coated in a durable epoxy powder coated finish.

### Considerations

- Offered in a range of sizes and foot prints see price guide.
- Static or mobile options available.
- Delivered fully assembled please ensure suitable access is available.

### Technical Information



Static leg detail



TPACS14 - Ø1400 x Ø1400  
TPACS08 - Ø800 x Ø800



TTICS16 - Ø800 x 1600 x Ø800  
TTICS08 - Ø800 x 1400 x Ø800



Mobile leg detail



TPACS14 - Ø1400 x Ø1400  
TPACS08 - Ø800 x Ø800




TTICS16 - Ø800 x 1600 x Ø800  
TTICS08 - Ø800 x 1400 x Ø800

Square edge



Conform to



Environment



Quality



100% Recyclable



Work Surface



Maximum Load  
Evenly Spread



Guarantee



Dimensions

For full details see our price guide