



GRESHAM



MODULAR CREDENZAS

PRODUCT DATA SPECIFICATION



GRESHAM

CREDENZA UNITS

PRODUCT DATA SPECIFICATION

A range of Credenza units. Available as a open unit or with Melamine faced chipboard doors or toughened glass doors.

Material

Top panel 25mm Thick Melamine faced chipboard. Tops are edged all around with 2mm thick impact resistant ABS.

Carcase 18mm Thick Melamine faced chipboard edged with 1mm thick impact resistant ABS.

Wooden Doors 18mm Thick Melamine faced chipboard edged with 2mm thick impact resistant ABS.

Glass doors 6mm thick toughened glass.

Steel frame 1 inch square mild steel tube with a 1.5mm wall thickness


Considerations

- Unit supplied with a steel frame.
- Units are desk high when not mounted on steel frame.
- Available as a open unit or with locking M.F.C. doors or non locking glass doors.
- Unit divided into 3 sections each section is supplied with an adjustable shelf.
- The locks are part of a suited system that have over 250 differs, can be supplied with a master key or can be keyed alike. Supplied with two keys; one of which has a collapsible fob.
- Supplied with adjustable feet to allow units to be levelled.
- A range of handle styles available.

Square edge



Certification



Environment



Quality



100% Recyclable



Surface



Guarantee



Dimensions

For full details see capacities