



GRESHAM



LS36

PRODUCT DATA SPECIFICATION



GRESHAM

LS36

PRODUCT DATA SPECIFICATION

LS36 combines one single shell with several different frames, creating a versatile and multipurpose seating family.

Materials

The LS36 features a single piece, injection moulded Polypropylene seat and back shell. This is moulded with threaded steel inserts that accept machine screws through moulded Polypropylene sockets, allowing a variety of bases to be fitted.

The LS36A has an 'A' frame style frame that is fully welded in the centre and is machined from Ø19mm of 1.5mm thick steel rod.





The LS36B is machined from Ø16mm of 2mm thick steel rod.

The LS36C and LS36D is fully welded in the centre and machined from Ø11mm of 1.5mm thick steel rod. Frame is fitted with glides.

Considerations

- Available in 4 different frame.
- Stool height available.
- Available in 6 bright plastic colours.
- Upholstered seat pad available in a variety of fabrics.
- Suitable for contract environments such as restaurants and cafes.

Technical Details

				
Model	LS36A	LS36B	LS36C	LS36D
OA Height	790	800	810	1105
OA Width	540	540	560	544
OA Depth	525	525	525	525
Seat Height	450	450	450	755



Environment



Conformity



Quality



100% Recyclable



Maximum Load
Per Seat



Fabric Choice
Upholstered Versions



Guarantee



Plastic Colours

