



GRESHAM



GOF SCREENS

PRODUCT DATA SPECIFICATION



GRESHAM

GOF SCREENS

PRODUCT DATA SPECIFICATION

Desk mounted screens can be used to reduce sound throughout a room whilst delineating personal space on desk clusters.

Materials

Manufactured using an extruded framework produced in 6063A T6 Aluminium alloy to BS1474. All screens are 30mm thick.

The substrate of the screens is produced from Medium Density Fibre Board which is laminated together using water-based adhesives. The resultant panel is machined to accept the support brackets that can be used to connect the screens to desk or table worksurfaces.

The panels are upholstered in a selection of fabric for choice. Each standard fabric complies with flammability requirements for contract use.

Glazed versions have a 3mm clear or frosted acrylic panel which is held in place by an aluminium frame matching the endposts.

Support brackets are produced in die-cast aluminium and are coated with a durable epoxy powder coating that can be colour matched to the metal framework of the adjacent desks the screens are used on.

Considerations

- Available in a selection of fabric colours, finishes and paint trim colours.
- Available in 380mm & 480mm heights, with straight and waved-topped options.
- Available in a selection of widths from 768mm to 1768mm.
- Available part /full acrylic or perforated steel / dry wipe.
- Available with a selection of optional shelves and accessories.
- Can be linked in straight lines, at 45 or 60 degree angles.

Environment	
Certification	
Quality	
100% Recyclable	
Fabric Choice	
Guarantee	