



GRESHAM



GD1

TABLES



GD1

TABLES

Available in two height variations, a selection of footprints and finishes, GD1 is at home any working landscape. The elegantly angled legs are producing in solid wood with an option for cleverly concealed cable control.



DINING

CODE	DESCRIPTION	WIDTH	DEPTH	HEIGHT
GD1A1	Non-powered	2000mm	1000mm	740mm
GD1A3	Powered	2000mm	1000mm	740mm
GD1B1	Non-powered	2400mm	1200mm	740mm
GD1B3	Powered	2400mm	1200mm	740mm
GD1C1	Non-powered	2800mm	1200mm	740mm
GD1C3	Powered	2800mm	1200mm	740mm
GD1D1	Non-powered	1600mm	1600mm	740mm
GD1D3	Cable Managed	1600mm	1600mm	740mm
GD1E1	Non-powered	1200mm	1200mm	740mm
GD1E3	Cable Managed	1200mm	1200mm	740mm
GD1F1	Non-powered	1000mm	1000mm	740mm
GD1F3	Cable Managed	1000mm	1000mm	740mm

GD1

TABLES



POSEUR

CODE	DESCRIPTION	WIDTH	DEPTH	HEIGHT
GD1A2	Non-powered	2000mm	1000mm	1040mm
GD1A4	Powered	2000mm	1000mm	1040mm
GD1B2	Non-powered	2400mm	1200mm	1040mm
GD1B4	Powered	2400mm	1200mm	1040mm
GD1C2	Non-powered	2800mm	1200mm	1040mm
GD1C4	Powered	2800mm	1200mm	1040mm
GD1D2	Non-powered	1600mm	1600mm	1040mm
GD1D4	Cable Managed	1600mm	1600mm	1040mm
GD1E2	Non-powered	1200mm	1200mm	1040mm
GD1E4	Cable Managed	1200mm	1200mm	1040mm
GD1F2	Non-powered	1000mm	1000mm	1040mm
GD1F4	Cable Managed	1000mm	1000mm	1040mm



FEATURES

- All legs fitted with adjustable feet to accommodate uneven floors
- Options for discreet cable control in two of four legs
- Tables available in dining (sit) and poseur (stand) height models
- Removable cable trays fitted to underframes
- Optional service modules can be fitted through worksurfaces
- Selection of worksurface and leg finishes
- Robust, stable construction for longevity of use

MATERIALS

25mm or 36mm worksurfaces produced in FSC certified substrates with either plastic laminate or wood veneered surface finishes. Plastic laminate tops are finished with a matching or contrasting 2mm thick impact resistant ABS edge detail. Veneered products have a matching wood veneer edge.

Worksurface sub-frames are produced in 60mm x 30mm tubular steel sections and die-cast aluminium elements used at joints and to support the tops, providing a durable and stable platform. Legs are connected to the underframe and the tops using fabricated pressed steel components. All metalwork is finished in a resilient black epoxy powder coating.

Legs are produced in solid Ash that are drilled and pre-fitted with threaded inserts providing 'metal-to-metal' fixing points that are strong and allow the tables to be assembled and disassembled multiple times without damage to the components. Wood based components are finished with a Natural Oak or Black acid catalyst lacquer as standard.

WOOD FRAME COLOURS



Black

Natural Oak

Environment



Quality



Maximum Load
Evenly distributed



Guarantee



Work Surface



*Further 'standards' certification available upon request.





GRESHAM

Head Office: Gresham Office Furniture Limited, Platinum Park, Lynstock Way, Horwich, Bolton, BL6 4SA | **Tel:** 01204 664422

London Showroom: 28 St John's Lane, Clerkenwell, London, EC1M 4BU | **Tel:** 020 7242 5709

WWW.GOF.CO.UK